

Technical Datasheet

DuPont™ Tyvek® Plastering Tape

Product Description & Application

High performance airtight, windtight and watertight adhesive tape for internal and external use, with a surface that provides a suitable key to receive plaster and/or render. Allows efficient airtight sealing at junctions between walls, floors and ceilings and around windows, doors and any penetrations in the building envelope. Tape has a moisture adaptive Sd value (vapour resistance) which helps to eliminate the risk of moisture being trapped within the building envelope.

Product composition

Carrier: Moisture adaptive special PET/PA non-woven film (white)
Adhesive: Acrylic
Liner: Siliconized PP film

Specifications

PROPERTY	VALUE
Stylename	1310PT
Colour	White
Thickness	approx. 400 µm
Basis weight	approx. 300 g/m ²
Temperature range	-40 °C to 100 °C
Installation temperature	> 0°C
Vapour transmission rate (Sd-value)	0,3 - 3 m depending on humidity level
Driving rain resistance* (EN 12208) (DIN 18542)	9A (600 Pa) meets BG 1
Airtightness** (DIN 4108-2) (DIN 18542)	airtight meets BG R
Tensile strength (MD and XD: DIN EN 14410)	approx. 40 N/cm
Elongation at break (MD and XD: DIN EN 14410)	approx. 15 %
Adhesion to steel	approx. 15 N/cm
* Tested on primed cemented surface as well as on PVC without primer.	
** Measured at a pressure difference of 600Pa. Tested on an aluminum surface.	

Use and Care Recommendations

- Easy installation due to split release liner and high tensile strength in length - and cross-direction
- Very good temperature resistance
- Free of emulsifiers and emulsifiers auxiliaries (APEO's)
- Solvent free adhesive with very low emissions and excellent ageing resistance
- Outdoor exposure up to 3 months (not sensitive to contact with water)
- Can be easily plastered
- Conditions: store rolls in their initial packaging, flat, in a clean and dry place.
- Storage temperature between +5 °C & 35 °C and away from direct sunlight.
- The surface should be free from dirt, moisture, ice, grease and other materials which could potentially reduce adhesion strength
- In cases where adhesion is not effective due to the surface of the building material being very porous, non-stable, chalky or sandy the DuPont™ Tyvek® Primer 1310P is recommended beforehand

Date: April 14, 2020

DuPont de Nemours
(Luxembourg) S.à r.l.
Rue General Patton,
L - 2984 Luxembourg
Tel.: +352 3666 5885
tyvek.info@lux.dupont.com

www.building.dupont.co.uk

This information corresponds to our current knowledge on the subject. It is not intended to substitute for any testing you may need to conduct to determine for yourself the suitability of our products for any application other than the application as specified herein. This information may be subject to revision as new knowledge and experience becomes available. Since we cannot anticipate all variations in actual end-use conditions, DuPont makes no warranties and assumes no liabilities in connection with any use of this information for applications other than the application as specified herein. Nothing in this publication is to be considered as a license to operate under or a recommendation to infringe any patent right. Product safety information is available on request. This data sheet is a printed document and is valid without signature.

DUPONT
Tyvek®