

USYSTEM

ROOF SW EASY AIRTIGHT



Elementtype	Rc-waarde [m²K/W]	Aantal velden	Dakhelling											
			15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°
ROOF SW EASY AIRTIGHT CB White CB Green PLY F Wood Origin Wood Shelf	4,7	1-velds	1620	1870	1870	1900	1900	1890	1880	1870	1930	2000	2080	2170
		meervelds*	1820	2120	2120	2140	2150	2130	2120	2110	2180	2270	2360	2470
		overstek	360	420	420	420	430	420	420	420	430	450	470	490
	5	1-velds	1810	1960	1975	1990	1985	1980	1970	1960	2100	2240	2305	2370
		meervelds*	2030	2500	2370	2240	2235	2230	2220	2210	2370	2530	2605	2680
		overstek	406	500	474	448	447	446	444	442	474	506	521	536
	6,3	1-velds	1980	2280	2280	2310	2320	2300	2290	2290	2360	2440	2540	2650
		meervelds*	2210	2570	2570	2600	2610	2590	2580	2570	2660	2760	2870	3000
		overstek	440	510	510	520	520	510	510	510	530	550	570	600
	7	1-velds	2200	2520	2530	2560	2560	2550	2540	2530	2610	2710	2810	2930
		meervelds*	2450	2840	2840	2880	2890	2860	2850	2840	2940	3050	3180	3320
		overstek	490	560	560	570	570	570	570	560	580	610	630	660
	8	1-velds	2480	2830	2830	2870	2880	2860	2850	2850	2940	3040	3160	3300
		meervelds*	2750	3180	3190	3230	3240	3220	3200	3200	3310	3430	3570	3740
		overstek	550	630	630	640	640	640	640	640	660	680	710	740

Uitgangspunten: Windgebied 2 onbebouwd
 Dakbedekking: 50 kg/m²
 * Bij meervelds overspanning moet het kleinere veld tenminste 1/3 van het grotere veld bedragen