

USYSTEM

ROOF OS COMFORT



Elementtype	Rib-afmetingen [mm]	Aantal velden	Dakhelling											
			15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°
ROOF OS COMFORT CB Green CB White PLY P PLY F Wood Wood Shelf Wood Origin	28 x 153	1-velds	3010	3220	3235	3250	3255	3260	3265	3270	3275	3280	3285	3290
		meervelds*	4140	4250	4390	4530	4505	4480	4445	4410	4375	4340	4305	4270
		overstek	1035	1063	1098	1133	1126	1120	1111	1103	1094	1085	1076	1068
	28 x 172	1-velds	3915	3940	3965	3990	3995	4000	4010	4020	4020	4020	4025	4030
		meervelds*	5540	5550	5560	5570	5535	5500	5460	5420	5420	5420	5400	5380
		overstek	1385	1388	1390	1393	1384	1375	1365	1355	1355	1355	1350	1345
	28 x 196	1-velds	4300	4580	4600	4630	4650	4650	4660	4670	4770	4870	5000	5140
		meervelds*	5930	6000	6000	6000	6000	6000	6000	6000	6000	6000	6000	6000
		overstek	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500
	28 x 215	1-velds	4300	5000	5035	5070	5155	5240	5180	5120	5120	5120	5090	5060
		meervelds*	5930	6000	6000	6000	6000	6000	6000	6000	6000	6000	6000	6000
		overstek	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500

Uitgangspunten: Windgebied 2 onbebouwd
Dakbedekking: 50 kg/m²
* Bij meervelds overspanning moet het kleinere veld tenminste 1/3 van het grotere veld bedragen