

USYSTEM

ROOF OS EASY AIRTIGHT



Elementtype	Ribhoogte [mm]	Aantal velden	Dakhelling											
			15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°
ROOF OS EASY AIRTIGHT CB Green CB White PLY F	145	1-velds	2930	3130	3140	3170	3180	3180	3180	3190	3250	3330	3410	3510
		meervelds*	4040	4420	4410	4430	4420	4380	4340	4320	4380	4450	4520	4610
		overstek	1010	1100	1100	1100	1100	1090	1080	1080	1090	1110	1130	1150
	170	1-velds	3450	3680	3690	3720	3740	3740	3740	3750	3820	3910	4010	4120
		meervelds*	4750	5190	5180	5200	5190	5140	5100	5070	5140	5230	5320	5420
		overstek	1180	1290	1290	1300	1290	1280	1270	1260	1280	1300	1330	1350
	196	1-velds	4040	4320	4330	4360	4380	4380	4390	4400	4490	4590	4700	4840
		meervelds*	5580	6000	6000	6000	6000	6000	5990	5950	6000	6000	6000	6000
		overstek	1390	1520	1520	1520	1520	1510	1490	1480	1510	1530	1560	1590
	221	1-velds	4490	4790	4800	4840	4860	4860	4870	4880	4980	5100	5230	5380
		meervelds*	6000	6000	6000	6000	6000	6000	6000	6000	6000	6000	6000	6000
		overstek	1550	1690	1680	1690	1690	1670	1660	1650	1670	1700	1730	1760
	246	1-velds	5170	5510	5530	5570	5600	5600	5610	5630	5740	5870	6000	6000
		meervelds*	6000	6000	6000	6000	6000	6000	6000	6000	6000	6000	6000	6000
		overstek	1790	1950	1940	1950	1950	1930	1920	1910	1930	1960	2000	2040

Uitgangspunten: Windgebied 2 onbebouwd
 Dakbedekking: 50 kg/m²
 * Bij meervelds overspanning moet het kleinere veld tenminste 1/3 van het grotere veld bedragen