

USYSTEM

ROOF DS EASY AIRTIGHT



Elementtype	Rib-afmetingen [mm]	Aantal velden	Dakhelling											
			15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°
ROOF DS EASY AIRTIGHT CB Green CB White PLY F	24 x 145	1-velds	3750	4040	4060	4080	4075	4070	4065	4060	4135	4210	4245	4280
		meervelds*	4670	5030	5045	5060	5060	5060	5050	5040	4675	4310	4123	3935
		overstek	1168	1258	1261	1265	1265	1265	1263	1260	1169	1078	1031	984
	24 x 170	1-velds	4300	4640	4655	4670	4665	4660	4650	4640	4730	4820	4860	4900
		meervelds*	5340	5750	5770	5790	5785	5780	5770	5760	5865	5970	6018	6065
		overstek	1335	1438	1443	1448	1446	1445	1443	1440	1466	1493	1500	1500
	24 x 192	1-velds	4710	5080	5100	5120	5105	5090	5085	5080	5175	5270	5315	5360
		meervelds*	5830	6000	6000	6000	6000	6000	6000	6000	6000	6000	6000	6000
		overstek	1458	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500
	28 x 221	1-velds	5430	5250	5475	5700	5690	5680	5670	5660	5830	6000	6080	6160
		meervelds*	6000	6000	6000	6000	6000	6000	6000	6000	6000	6000	6000	6000
		overstek	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500
	24 x 245	1-velds	5790	6000	6000	6000	6000	6000	6000	6000	6000	6000	6000	6000
		meervelds*	6000	6000	6000	6000	6000	6000	6000	6000	6000	6000	6000	6000
		overstek	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500
	24 x 272	1-velds	6000	6000	6000	6000	6000	6000	6000	6000	6000	6000	6000	6000
		meervelds*	6000	6000	6000	6000	6000	6000	6000	6000	6000	6000	6000	6000
		overstek	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500	1500

Uitgangspunten: Windgebied 2 onbebouwd
Dakbedekking: 50 kg/m²
* Bij meervelds overspanning moet het kleinere veld tenminste 1/3 van het grotere veld bedragen